













Series M Configuration Images by Part

 <p>Figure 1 Multi-Turn Potentiometer PN 4100-01 / -22 / -43</p>	 <p>Figure 2 Multi-Turn Potentiometer with Base PN 4100-08 / -29 / -50</p>	 <p>Figure 3 Multi-Turn Potentiometer with RoundAbout™ PN 4100-15 / -36 / -57</p>
 <p>Figure 4 Single Turn Potentiometer PN 4100-64</p>	 <p>Figure 5 Single Turn Potentiometer with Base PN 4100-71</p>	 <p>Figure 6 Single Turn Potentiometer with RoundAbout™ PN 4100-78</p>
 <p>Figure 7 134.4-Line Encoder PN 4100-85 / -86</p>	 <p>Figure 8 134.4-Line Encoder with Base PN 4100-88 / -89</p>	 <p>Figure 9 134.4-Line Encoder with RoundAbout™ PN 4100-91 / -92</p>
 <p>Figure 10 3674-Line Encoder PN 4100-97 / -98</p>	 <p>Figure 11 3674-Line Encoder with Base PN 4100-99 / -100</p>	 <p>Figure 12 3674-Line Encoder with Base & RoundAbout™ PN 4100-101 / -102</p>

Series M Configuration Images by Part



 <p>Figure 13 Potentiometer with Flying Leads PN 4100-02 / -23 / -44 / -65</p>	 <p>Figure 14 Potentiometer with Flying Leads and Base PN 4100-09 / -30 / -51 / -72</p>	 <p>Figure 15 Potentiometer with Flying Leads and RoundAbout™ PN 4100-16 / -37 / -58 / -79</p>
 <p>Figure 16 Potentiometer with MS3102 Connector PN 4100-03/-24/-45/-66/-87/-94</p>	 <p>Figure 17 Potentiometer with MS3102 Connector and Base PN 4100-10/-31/-52/-73/-90/-95</p>	 <p>Figure 18 Potentiometer with MS3102 Connector and RoundAbout™ PN 4100-17/-38/-59/-80/-93/-96</p>
 <p>Figure 19 Signal Conditioner with MS3101 Connector PN 4100-04/-05/-25/-26/-46/-47/-67/-68</p>	 <p>Figure 20 Signal Conditioner with MS3101 Connector and Base PN 4100-11/-12/-32/-33/-53/-54/-74/-75</p>	 <p>Figure 21 Signal Conditioner with MS3101 Connector and RoundAbout™ PN 4100-18/-19/-39/-40/-60/-61/-81/-82</p>
 <p>Figure 22 Signal Conditioner with Flying Leads PN 4100-06/-07/-27/-28/-48/-49/-69/-70</p>	 <p>Figure 23 Signal Conditioner with Flying Leads and Base PN 4100-13/-14/-34/-35/-55/-56/-76/-77</p>	 <p>Figure 24 Signal Conditioner with Flying Leads and RoundAbout™ PN 4100-20/-21/-41/-42/-62/-63/-83/-84</p>